

SAFETY DATA SHEET

1 of 8 MCL-AIRBOND

Prepared to OSHA, ANSI, NOHSC, WHMIS, 1002/58 & 1272/2008/EC Standards SDS Revision: 4.2

SDS Revision Date: 13/09/2021

	1. PRODUCT INDENTIFICATIO	N				
1.1	Product Name:					
	LIGHT ELEGANCE AirBond					
1.2	Chemical Name: BONDING RESIN	Australian Importer:				
1.3	Synonyms:	ABN 75 105 168 045				
1.4	NA Trade Names:	Unit 2, 33-35 Lundberg Dr Murwillumbah NSW 2484				
	none	Ph 1300 739893				
1.5	Product Use: PROFESSIONAL USE ONLY	24 hrs contact : 0414362966				
1.6	Manufacturer's Name:	Email : info@beautyworld.com.au				
4 7	MCCONNELL LABS, INC.	Web: www.beautyworld.com.au				
1.7	Manufacturer's Adress: 406 SW UMATILLA AVE, REDMOND, OR 97756 USA					
1.8	Emergency Phone:					
	CHEMTREC: +1 703 527 3887 / +1 800 424 9300 (CCN 696869)					
1.9	Business Phone / Fax:					
	+1 541 526 1417 / +1 541 526 1418					
	2. HAZARD INDENTIFICATION	l				
2.1	Hazard Identification:					
	cause an allergic skin reaction. H320 - Causes eye irritation. Precautionary Statements (P): P210 - Keep away from heat/sparks/open flame/hot surfaces - No Smoking. P223 - Keep container tightly closed. P243 - Take precaustionary measures against static discharge. P261 - Avoid breathing fumes/gas/vapors/spray. P272 - Contaiminated work clothing should not be allowed out of the workplace. P280 - Wear protective gloves. P302 + P352 - IF ON SKIN - wash with soap and warm water. P305 + P351 + P338 - IF IN EYES - Rince continually with water for several minutes. Remove contact lenses if present and easy to do, continue rinsing. P333 + P313 - If skin reaction or a rash occurs, get medical attention. P337 + P313 - ilf eye irritation persists, P321 - for specific first aid treatment (see section 4 of this Safety Data Sheet). P363 - Wash contaminated clothing before resuse. P501 - Dispose of contents/container to a licensed treatment, storage or disposal facility (TSDF).					
2.2	Routes of Entry: Inhalation: YES Absorption: YES Inge	stion: YES				
2.3	Effects of Exposure: INGESTION: If product is swallowed, may cause nausea, vomiting and/or diarrhea and centr EYES & SKIN: The liquid may produce eye discomfort and is capable of causing temporary impulceration. The vapor is discomforting to the eye. Splashes may cause severe e Moderately irritating to the eyes. Symptoms of overexposure may include redn the skin, especially after prolonged contact. The product can cause allergic skin or repeated expsoure. INHALATION: Vapors of this product may be moderately irritating to the nose, throat and oth overexposure can include coughing, wheezing, nasal congestion and difficulty b central nervous system depression (e.g., drowsiness, headaches, nausea).	pairment of vision and/or transient eye inflamation, eye irritation, possible corneal burns and eye damage. ess, itching, irritation and watering. May be irritating to reactions (e.g., rashes, welts, dermatitis) upon prolonged er tissues of the respiratory system. Symptoms of reathing. Inhalation of concentrated vaors can cause				
2.4	Symptoms of Overexposure: Symptoms of skin overexposure may include redness, itiching and irritation of affected areas. Ove watering. The product can cause allergic skin reactions (e.g., rashes, welts, deratitis) upon prolong					
	Acute Health Effects: Moderate irritation to eyes near affected areas. Additionally, high concentrations of vapo nausea.	rs can cause drowsiness, dizziness, headaches and				
2.6	Chronic Health Effects:					
2.7	The material may cause an allergic reaction for some sensitive individuals. Target Organs:					

Eyes, skin

	3. COMPOSITION & INGREDIENT INFORMATION 2 of 8												
					EXPO	SURE L	IMITS	N AIR	(mg/m	3)			
					AC	GIH		NOHS	2		OSHA		
					р	pm		ppm			ppm		
							ES-	ES-	ES-				
CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	TWA	STEL	PEAK	PEL	STEL	IDLH	OTHER
ETHYL ACETATE	141-86-4	AH5425000	205-500-4	60-100	400	400	200	400	NF	NA	NA	2000	400 TWA
	Flamm.Lig.2; Eye I	rrit. 2; STOT S	SE 3, H224, H3	19, H336									
METHACRYLOXYOPROPYL	2530-85-0	UC230000	219-785-8	5-10	NA	NA	NF	NF	NF	NA	NA	NA	
TRIMETHYLOXYSILANE													
			00 0										

4. FIRST AID MEASURES 4.1 First Aid: INGESTION: If ingested, do not induce vomiting! If product has been swallowed, drink plenty of water or milk IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give water or milk to an unconscious person. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed. SKIN & EYES: If product gets in the eyes, flush with copious amounts of lukewarm water for at least 15 minutes. Open and close eyelid(s) to ensure thorough irrigation. Seek immediate medical attention. If problem persists, seek immediate medical attention. If irritation occurs & product is on the skin, rinse thoroughly with lukewarm water followed by a thorough washing of the affected area with plenty of soak and waster. Remove all contaminated clothing including footwear and wash thoroughly before reuse. If irritation, redness or swelling persists, consult a physician immediately. INHALATION: Remove victim to fresh air at once. If breathing stops, perform artificial respiration. Seek immediate medical attention. HEALTH 4.2 Medical Conditions Aggravated by Exposure: 1 Pre-existing dermatitis, other skin conditions and disorders of the target organs (eyes, skin) FLAMMABILITY 3 **PHYSICAL HAZARDS** 1 PROTECTIVE EQUIPMENT В EYES SKIN

5. FIREFIGHTING MEASURES

Upper Explosive Limit (UEL): NA

5.1 Flashpoint & Method: - 20 °C (-4 °F) calculated

5.2 Autoignition Temperature:

NA

5.3 Flammability Limits:5.4 Fire & Explosion Hazards:

This product is slightly flammable. When involved in a fire, this product may ignite and decompose to form toxic gases (e.g., CO, CO2 and Nox)

Lower Explosive Limit (LEL): NA

5.5 Extinguishing Methods:

Water, Foam, CO2, Dry Chemical

5.6 Fire Fighting Procedures:

First responders should wear eye protection. Structural fire fighters must wear full protective equipment and MSHA/NIOSH approved, self-contained breathing apparatus. If possible, prevent runoff water from entering storm drains, bodies of water or other enviormentally sensitive reas. If necessary, rinse contaminated equipment with soapy water before returnign to service.

6. ACCIDENTAL RELEASE MEASURES

6.1 Spills:

Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment. For small spills (e.g., , 1 gallon [3.785 liters]) wear appropriate personal protective equipment (e.g., goggles & gloves). Maximize ventilation (open doors and windows). Expose spilled material to UV light source for 2-5 minutes. Lift cured material from substrate and repeat until very little residue remains. Remove remaining spilled material with absorbent material and place into appropriate closed container(s). Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with warm, soapy water. Remove any contaminated clothing and wash before reuse. For large spills (e.g., > 1 gallon [3.785 liters]) deny entery to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Expose spilled material to UV light source for 2-5 minutes. Lift cured material from substrate and repeat until very little residue remains. Remove remaining spilled material to UV light source for 2-5 minutes. Lift cured material from substrate and repeat until very little residue remains. Remove remaining spilled material to UV light source for 2-5 minutes. Lift cured material from substrate and repeat until very little residue remains. Remove remaining spilled material with absorbent material and place into appropriate closed container(s). Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with warm, soapy water. Remove any contaminated clothing and wash before reuse. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water.

7. HANDLING AND STORAGE INFORMATION

7.1 Work & Hygiene Practices:

Avoid prolonged contact with this material. Avoid breathing the vapors generated by this product. Use in a well ventilated location (e.g., local exhaust ventilation, fans). Wash exposed skin thoroughly with plenty of soap and water after using this product. If necessary, use a moisturizer after washing. Do not eat, drink or smoke while handling this product.

7.2 Storage & Handling:

Use and store in a cool, dry, well ventilated location. Keep away from excessive heat. Keep away from incompatible materials listed in Section 10. Do not store in damaged or unmarked containers or storage devises. Keep containers securely closed when not in use. Open slowly on a level, stable surface. Empty containers may contain residual amounts of this product; therefore, empty containers shoiuld be handled with care. As a precaution against exposure to the eyes, nose, throat and face, this product should not be stored higher than waist level. KEEP AWAY FROM CHILDREN AT ALL TIMES!

7.3 Special Precautions:

Do not store where temperatures can exceed 50 °C (122 °F).

3 of 8

	8. E	XPOSURE CONTROLS & PERSONAL PROTECTION	4 of 8	
8.1 Ventilation & Engineering Controls: Use with adequate ventilation (e.g., local exhaust ventilation, fans). Ensure appropriate decon equipment is available (e.g., sink, safety shower, eye wash station).				
8.2	Respiratory Protection:	No special respiratory protections is required under typical circumstances of use or handling. In instances where vapors or sprays of this product are generated, and		
		respiratory protection is needed, use only protection authorized by 29 CFR § 1910.134, application U.S. State regulations or the Candaian CAS Standard Z94.4-93 and applicable standards of Canadian Provinces, EC Member States or Australia.		
8.3	Eye Protection:	Wear protective eyewear (e.g., safety glasses with side shields) at all times when handling this product. Always use protective eyewear when cleaning spills or leaks. Contact lenses pose a special hazard; soft lenses may absorb and concentrate irritants.	0	
8.4	Hand Protection:	None required under normal conditions of use. However, may cause skin irritation in some sensitive individuals. When handling large quantities (e.g., >1 gallon [3.785 liters]), wear nitrile or imprevious gloves.		
8.5	Body Protection:	No apron required when handling small quantities. When handling large quantities (e.g., . 1 gallon), eye wash stations and deluge showers should be available. Upon completion of work activities involving large quantities of this product, wash any exposed areas thoroughly with soap and water.		

	9. PHYSICAL & CHEMICAL PROPERTIES					
9.1	Density:	0.9				
9.2	Boiling Point:	57 °C (134 °F)				
9.3	Melting Point:	ND				
9.4	Evaporation Rate:	NA				
9.5	Vapor Pressure:	30.6 kPa @ 25°C				
9.6	Appearance & Color:	Clear liquid				
9.7	Odor Threashold:	NE				
9.8	Solubility:	Not soluble				
9.9	pH:	NA				
9.1	Viscosity:	approximately 300 cps				
9.11	Flash Point:	- 20 °C (-4 °F) calculated				
9.12	Other Information:	NA				

10. STABILITY & REACTIVITY

10.1	Stability:
	Relatively stable under ambient conditions when stored properly.
10.2	Hazardous Decomposition Products:
	If exposed to extremely high temperatures, products of thermal decomposition may include irritating vapors and toxic gases (e.g., oxides of
	carbon and nitrogen).
10.3	Hazardous Polymerization:
	Will not occur.
10.4	Conditions to Avoid:
	Exposure or contact to extreme temperatures, incompatable chemicals, strong light sources, sparks and flame.
10.5	Incompatable Substances:
	Strong oxidizers, peroxides, strong acids or alkalis.

11. TOXICOLOGICAL INFORMATION

11.1	Toxicity Data:
	This product has NOT been tested on animals to obtain toxicology data. There are toxicology data for the components of the produt which are
	found in scientific literature. These data have not been presented in this document.
11.2	Acute Toxicity:
	See Section 2.5
11.3	Chronic Toxicity:
	See Section 2.6
11.4	Suspected Carcinogen:
	The ingredients of this product are not listed as carcinogens by the National Toxicology Program and have not been evaluated by the Internail
	Agency for Research on Cancer or the American Conference of Government Industrial Hygenists.
11.5	Reproductive Toxicity:
	This product is not reported to cause reproductive toxicity in humans.
	Mutagenicity:
	This product is not reported to produce mutagenic effects in humans.
	Embryotoxicity:
	This product is not reported to produce embryotoxic effects in humans.
	Teratogenicity:
	This products is not reported to cause teratogenic effects in humans.
11.6	Irritancy of Product:
	See Section 2.3
11.7	Biological Exposure Indicies:
	NE
11.8	Physician Recommendations:
	Treat syptomatically
	12. ECOLOGICAL INFORMATION
12.1	Environmental Stability:
	This product will slowly volatile from soil. Components of this product will slowly decompose into organic compounds. Butyl Acetate: K _{oc} =
	1.82. Water Solubility: 120 parts H_2O at 25 °C (77 °F). Bioconcentration Factor = 4-14. Bioconcentration is not anticipated to be significant.
	This compound can be removed from contaminated environments from volatilization and biodegredation. This compound's half life is 6.1
	hours.
12.2	Effects on Plants & Animals:
	There is no specific data availble for this product on plant life.
12.3	Effects on Aquatic Life:
	There is no specific data availble for this product on aquatic life.
	13. DISPOSAL CONSIDERATIONS
13.1	Waste Disposal:
	Dispose inaccordance with local, state and Federal waste laws.
13.2	Special Considerations:
	This material becomes an inert plastic upon prolonged exposure to sources of UV light and sunlight. Disposal of inert plastics is safer for the
	environment and is more easily handled for disposal according to local, state and Federal regulations.

environment and is more easily handled for disposal according to local, state and Federal regulations.

	14. TRANSPORTATION INFORMATION 6 of 8
The b	asic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation.
Addit	onal descriptive information may be required by 49 CFR, IATA/ICAO, IMDG, SCT, ADR and the CTDGR.
14.1	49 CFR (GRD):
	ID8000 CONSUMER COMMODITY, 9 (IP VOL ≤ 0.5 L) - UNTIL 12/31/2020
	UN1173, ETHYL ACETATE SOLUTION, 3, II, LTD QTY (IP VOL ≤ 0.5 L)
14.2	IATA (AIR):
	ID8000, CONSUMER COMMODITY, 9 (IP VOL ≤ 0.5 L)
	UN1173, ETHYL ACETATE SOLUTION, 3, II, LTD QTY (IP VOL ≤ 0.5 L)
14.3	IMDG (OCN):
	UN1173, ETHYL ACETATE SOLUTION, 3, II, LTD QTY (IP VOL ≤ 0.5 L)
14.4	TDGR (Canadian GND):
	MARK PACKAGE "LIMITED QUANTITY" OR "QUANTITE LIMUTEE" OR "LTD QTY" OR "QUANT LTEE" (IP VOL ≤ 5.0 L)
	UN1173, ETHYL ACETATE SOLUTION, 3, II, LTD QTY (IP VOL ≤ 0.5 L)
14.5	ADR/RID (EU):
	UN1173, ETHYL ACETATE SOLUTION, 3, II, LTD QTY (IP VOL ≤ 0.5 L)
14.6	MEXICO (SCT):
	UN1173, ETHYL ACETATE SOLUCIÓN, 3, II, CANTIDAD LIMITADA (IP VOL ≤ 0.5 L)
14.7	ADGR (AUS):
	UN1173, ETHYL ACETATE SOLUTION, 3, II, LTD QTY (IP VOL ≤ 0.5 L)
	15. REGULATORY INFORMATION
15.1	SARA Reporting:
	ΝΑ
15.2	SARA Threshold Planning Quantity:
	NA
15.3	TSCA Inventory Status:
	All components of this product are listed in the TSCA Inventory or are exempt
15.4	CERCLA Reportable Quantity (RQ):
	ETHYL ACETATE: 5,0000 lbs (2,270 kg)
15.5	Other Federal Requirements:
	This products complies with the appropriate sections of the Food and Drug Administration's 21 CFR subchapter G (Cosmetics).
15.6	Other Canadian Regulations:
	This product has been classified according to the hazard criteria of the CPR and the SDS contains all of the information
	required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product 🛛 💙 🔮
	are on the Priorities Substances List.
15.7	State Regulatory Information:
	Ethyl Acetate is listed on the following state criteria list(s): Deleware Air Quality Management List (DE), Massachusetts Hazardous Substances
	List (MA), Minnesota Hazardous Substances List (MN), New Jersery Right-to-Know List (NJ), Pennsylvania Right-to-Know List (PA), and
	Washington Permissible Exposure Limits for Air Contaminants (WA).
	No other ingredients in this producd, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists:
	California Proposition 65 (CA), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous
	Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances list, (MN), New Jersey Right-to-Know List (NJ),
	new Yord Hazardous Substances List (NY), Pennsylvania Right-to-Know list (PA), Washington Permissible Exposures List (WA), Wisconsin
	Hazardous Substances List (WI)
15.8	67/548/EEC (European Union), Australian NOHSC:2011 (2003), and GHS Requirements:
	The primary cononents of this product are not listed in Annex 1 of EU Directive 67/548/EEC.
	Ethyl Acetate: Flammable (F). Harmful (Xi).
	Risk Phrases (R): 11-36/37/38 - Highly Flammable. Irritating to eyes, skin and respiratory system. Safety Phrases (S): 2-23-
	29 - Keep out of reach of Children. Do not breath gas, fumes, vapor or spray. Do not empty into drains. Keep away from
	sources of ignition - No Smoking. Avoid contact with skin and eyes, rinse immediately with plenty of water and seek
	medical advice.

16. OTHER INFORMATION

16.1 Other Information:	ACTION CALISES FYE IRRITATION Avoid breathing fume gas mist vanors snrav Wear				
	WARNING! MAY CAUSE AN ALLERGIC SKIN REACTION. CAUSES EYE IRRITATION. Avoid breathing fume, gas, mist, vapors, spray. Wear potective gloves and eye/face protection. IF ON SKIN - Wash with soap and water. IF IN EYES - Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing. If skin irritation or a rash occurs - get medical advice/attention.				
	and open flame. KEEP OUT OF THE REACH OF CHILDREN.				
16.2 Terms & Definitions:					
Please see last page of this SDS.					
16.3 Disclaimer:					
must be reviewed for applicability to this produce reliable and accurate as of the date it was preptype, either expressed or implied, are provided	t to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other governemen regulations act. To the best of Shipmate's and McConnell Labs' knowledge, the information contained herein is ared; however, accuracy, suitability or completeness are not guaranteed and no warranties of any . The information contained herein relates only to the specific product(s). If this product(s) is properties must be considered. Data may be changed from time to time. Be sure to sonsult the				
16.4 Prepared for:					
McConnell Labs, Inc.					
406 SW Umatilla Ave					
Redmond, OR 97756 USA	McConnellLabs				
Tel: +1 541 526 1417					
Fax: +1 541 526 1418					
http://www.lightelegance.com					
16.5 Prepared by:					
ShipMate, Inc.					
PO Box 787					
Sisters, OR 97759-0787 USA Tel: +1 541 370 3600	ShinMate				
Fax: +1 541 370 5700	Damberaus Gends				
email: shipmate@shipmate.com	Training & Consulting				
Ternan sinpinate@sinpinate.com	_1				

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following: GENERAL INFORMATION:

CAS No. Chemical Abstract Service Number

EXPOSURE LIMITS IN AIR:

ACGIH American Conference on Governmental Industrial Hygienists				
TLV	Threshold Limit Value			
OSHA U.S. Occupational Safety and Health Administration				
PEL	Permissible Exposure Limit			
IDLH	Immediately Dangerous to Life and Health			

FIRST AID MEASURES:


CPR	Cardiopulmonary resuscitation - method in which a person whose heart has
	stopped receives manual chest compressions and breathing to circulate blood
	and provide oxygen to the body.

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS

HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard	HEALTH
1	Slight Hazard	FLAMMABILITY
2	Moderate Hazard	PHYSICAL HAZARDS
3	Severe Hazard	PERSONAL PROTECTION
4	Extreme Hazard	

PERSONAL PROTECTION RATINGS:



OTHER STANDARD ABBREVIATIONS:


NA	Not Available	
NR	NR No Results	
NE Not Established		
ND Not Determined		
ML	Maximum Limit	
SCBA	Self-Contained Breathing Apparatus	

NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:						
Autoignition Minimum temperature required to initiate combustion in air with no other source of ignition						
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source					
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source					

HAZARD RATINGS:

0	Minimal Hazard			
1	Slight Hazard			
2	Moderate Hazard			
3 Severe Hazard				
4 Extreme Hazard				
ACD Acidic				
ALK	ALK Alkaline			
COR	Corrosive			
₩	Use No Water			
OX Oxidizer				
TREFOIL	Radioactive			



TOXICOLOGICAL INFORMATION:

LD ₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals				
	S				
LC ₅₀	Lethal concentration (gases) which kills 50% of the exposed animal				
ppm	Concentration expressed in parts of material per million parts				
TD _{to}	Lowest dose to cause a symptom				
TCLo	Lowest concentration to cause a symptom				
TD _{lo} , LD _{lo} , & LD _o or	Lowest dose (or concentration) to cause lethal or toxic effects				
TC, TC _o , LC _{lo} , & LC _o					
IARC	International Agency for Research on Cancer				
NTP	National Toxicology Program				
RTECS	Registry of Toxic Effects of Chemical Substances				
BCF	Bioconcentration Factor				
TLm	Median threshold limit				
log K _{ow} or log K _{oc}	Coefficient of Oil/Water Distribution				

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System				
DOT	T U.S. Department of Transportation				
тс	TC Transport Canada				
EPA	U.S. Environmental Protection Agency				
DSL	DSL Canadian Domestic Substance List				
NDSL	NDSL Canadian Non-Domestic Substance List				
PSL	PSL Canadian Priority Substances List				
TSCA	TSCA U.S. Toxic Substance Control Act				
EU	EU European Union (European Union Directive 67/548/EEC)				
WGK	WGK Wassergefährdungsklassen (German Water Hazard Class)				

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

0	۲	٨	$\textcircled{\begin{subarray}{c} \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \$	1	۲		Ŕ
Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

EC (67/548/EEC) INFORMATION:

1-4		N	te	8	*	×	×
С	E	F	N	0	т	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful

CLP/GHS (1272/2008/EC) PICTOGRAMS:

	٢	٢	\diamond					*
GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment