

SAFETY DATA SHEET

1 of 8 MCL-PowerBond

SDS Revision Date: 13/09/2021 Prepared to OSHA, ANSI, NOHSC, WHMIS, 1002/58 & 1272/2008/EC Standards | SDS Revision: 4.2

1. PRODUCT INDENTIFICATION 1.1 Product Name: LIGHT ELEGANCE PowerBond & P* Base Coat Chemical Name: Australian Importer: Beautyworld Ptv Ltd POLYURETHANE (METH)ACRYLATE PREPOLYMER RESIN BLEND ABN 75 105 168 045 1.3 Synonyms: NA Unit 2, 33-35 Lundberg Dr 1.4 Trade Names: Murwillumbah NSW 2484 P* Base Coat, PowerBond & Pink PowerBond Ph 1300 739893 1.5 Product Use: 24 hrs contact: 0414362966 PROFESSIONAL USE ONLY Email: info@beautyworld.com.au Manufacturer's Name: Web: www.beautyworld.com.au MCCONNELL LABS, INC. 1.7 Manufacturer's Adress: 406 SW UMATILLA AVE, REDMOND, OR 97756 USA Emergency Phone: CHEMTREC: +1 703 527 3887 / +1 800 424 9300 (CCN 696869) Business Phone / Fax:

2. HAZARD INDENTIFICATION

2.1 | Hazard Identification:

+1 541 526 1417 / +1 541 526 1418

This product is classified as a HAZARDOUS SUBSTANCE and as a DANGEROUS GOOD according to the classification criteria of NOHSC: 1008 (2004) and ADG Code (Australia). WARNING! MAY CAUSE AN ALLERGIC SKIN REACTION. AVOID SKIN CONTACT DUE TO SENSITIZING POTENTIAL. CAUSES EYE IRRITATION. Hazard Statements (H): H226 - Flammable liquid and vapor. H317 - May cause an allergic skin reaction. H320 - Causes eye irritation. Precautionary Statements (P): P210 - Keep away from heat/sparks/open flame/hot surfaces - No Smoking. P223 - Keep container tightly closed. P243 - Take precaustionary measures against static discharge. P261 - Avoid breathing fumes/gas/vapors/spray. P272 - Contaiminated work clothing should not be allowed out of the workplace. P280 - Wear protective gloves. P302 + P352 - IF ON SKIN - wash with soap and warm water. P305 + P351 + P338 - IF IN EYES - Rince continually with water for several minutes. Remove contact lenses if present and easy to do, continue rinsing. P333 + P313 - If skin reaction or a rash occurs, get medical attention. P337 + P313 - ilf eye irritation persists, P321 - for specific first aid treatment (see section 4 of this Safety Data Sheet). P363 - Wash contaminated clothing before resuse. P501 - Dispose of contents/container to a licensed treatment, storage or disposal facility (TSDF).



2.2 Routes of Entry: Inhalation: YES Absorption: YES Ingestion: YES

2.3 Effects of Exposure:

EYES & SKIN:

If product is swallowed, may cause nausea, vomiting and/or diarrhea and central nervouse system depression. INGESTION:

The liquid may produce eye discomfort and is capable of causing temporary impairment of vision and/or transient eye inflamation, ulceration. The vapor is discomforting to the eye. Splashes may cause severe eye irritation, possible corneal burns and eye damage. Moderately irritating to the eyes. Symptoms of overexposure may include redness, itching, irritation and watering. May be irritating to the skin, especially after prolonged contact. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged

or repeated expsoure.

INHALATION: Vapors of this product may be moderately irritating to the nose, throat and other tissues of the respiratory system. Symptoms of

overexposure can include coughing, wheezing, nasal congestion and difficulty breathing. Inhalation of concentrated vaors can cause central nervous system depression (e.g., drowsiness, headaches, nausea). Odor may give some warning of exposure but odor fatigue

may occur.

Symptoms of Overexposure:

Symptoms of skin overexposure may include redness, itiching and irritation of affected areas. Overexposure in eyes may cause redness, itching and watering. The product can cause allergic skin reactions (e.g., rashes, welts, deratitis) upon prolonged or repeated exposure.

Acute Health Effects:

Moderate irritation to eyes near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and

Chronic Health Effects:

The material may cause an allergic reaction for some sensitive individuals.

Target Organs:

Eyes, skin

		3. COM	POSITION	& INGRE	DIEN.	TINF	ORM	ATIO	N				2 of 8	
					EXPO	SURE L	IMITS	IN AIR	(mg/m	າ3)				
					AC	GIH		NOHS	С		OSHA	\		
					р	pm		ppm			ppm			
							ES-	ES-	ES-		Γ			
- \ \- /	CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	TWA	STEL	PEAK	PEL	STEL	IDLH	OTHER	
Bis-HEA Poly (propylene glycol)-53 / IPDI Copolymer	NA	NA	NA	10-40	NA	NA	NF	NF	NF	NA	NA	NA		
Isopropylideneiphenyl	1565-94-2	NA	216-367-7	5-40	NA	NA	NF	NF	NF	NA	NA	NA		
bisoxyhydroxypropyl														
Methacryloyloxyethanol Maleate	51978-15-5	NA	NA	5-40	NA	NA	NF	NF	NF	NA	NA	NA		
Hydroxypropyl	27813-02-1	NA	NA	5-30	NA	NA	NF	NF	NF	NA	NA	NA		
Methacrylate														
Bis-HEMA Poly(neopentyl glycol adipate) / IPDI copolymer	NA	NA	NA	5-20	NA	NA	NF	NF	NF	NA	NA	NA L		
Methacryloyloxyethanol	868-77-9	NA	NA	0-10	NA	NA	NF	NF	NF	NA	NA	NA		
ТМРТМА	3290-92-4	NA	NA	0-8	NA	NA	NF	NF	NF	NA	NA	NA		
Methacrylic Acid	79-41-4	NA	NA	0-5	NA	NA	NF	NF	NF	NA	NA	NA		
Ethyl Acetate	141-78-6	AF7350000	205-500-4	0-5	150	200	150	200	INF	200	200	1700		
		uid 3; Specific Ta						•			1	1 = 1 = 1		
1-Hydroxycyclohexyl	947-13-3	NA	213-426-9	≤1.0	NA	NA	NF	NF	NF	NA	NA	NA		
phenylketone		al 5; Aquatic Acu	1		1	1	1	1	T	1	1	1		
Trimethylnenzoyl Diphenylphosphine Oxide	75980-60-8	NA	278-355-8	≤1.0	NA	NA	NF	NF	NF	NA	NA	NA		
CI 15850 (Red 6)	17852-98-1	NA	241-806-4	≤0.1	NA	NA	NF	NF	NF	NA	NA	NA		
			4. FIRS	T AID N	IEAS	URE	S							
4.1 First Aid: INGESTION:	_	not induce vom	water or milk		water	or mil	lk to ar	n unco	nsciou	s pers			-	

	4. FIRST AID MEASURES				
4.1	First Aid:				
	INGESTION: If ingested, do not induce vomiting! If product has been swallowed, drink plenty of water or milk IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give water or milk to an unconscious person. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed.			ne nearest Poison	
	SKIN & EYES: If product gets in the eyes, flush with copious amounts of lukewarm water for at least 15 minutes. Open and close eyelid(s) to ensure thorough irrigation. Seek immediate medical attention. If problem persists, seek immediate medical attention. If irritation occurs & product is on the skin, rinse thoroughly with lukewarm water followed by a thorough washing of the affected area with plenty of soak and waster. Remove all contaminated clothing including footwear and wash thoroughly before reuse. If irritation, redness or swelling persists, consult a physician immediately.				
	INHALATION:	Remove victim to fresh air at once. If breathing stops, perform artificial res	spiration. Seek immediate medi	cal attention.	
4.2	Medical Condition	ons Aggravated by Exposure:	HEALTH	1	
	Pre-existing der	matitis, other skin conditions and disorders of the target organs (eyes, skin)	FLAMMABILITY	0	
			PHYSICAL HAZARDS	1	
			PROTECTIVE EQUIPMENT	В	
			EYES SKIN		

	5. FIREFIGHTING MEASURES	3 of 8
5.1	Flashpoint & Method: > 100 °C (ASTM D93-15)	
5.2	Autoignition Temperature: NA	
5.3	Flammability Limits: Lower Explosive Limit (LEL): NA Upper Explosive Limit (UEL): NA	
5.4	Fire & Explosion Hazards: When involved in a fire, this product may ignite and decompose to form toxic gases (e.g., CO, CO2 and Nox)	
5.5	Extinguishing Methods: Water, Foam, CO2, Dry Chemical	
5.6	Fire Fighting Procedures: First responders should wear eye protection. Structural fire fighters must wear full protective equipment and MSHA/NIOSH approved, self-contained breathing apparatus. If possible, prevent runoff water from entering storm drains, bodies of water or other enviormentally sensitive reas. If necessary, rinse contaminated equipment with soapy water	

6. ACCIDENTAL RELEASE MEASURES

6.1 Spills:

Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment. For small spills (e.g., , 1 gallon [3.785 liters]) wear appropriate personal protective equipment (e.g., goggles & gloves). Maximize ventilation (open doors and windows). Expose spilled material to UV light source for 2-5 minutes. Lift cured material from substrate and repeat until very little residue remains. Remove remaining spilled material with absorbent material and place into appropriate closed container(s). Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with warm, soapy water. Remove any contaminated clothing and wash before reuse. For large spills (e.g., > 1 gallon [3.785 liters]) deny entery to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Expose spilled material to UV light source for 2-5 minutes. Lift cured material from substrate and repeat until very little residue remains. Remove remaining spilled material with absorbent material and place into appropriate closed container(s). Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with warm, soapy water. Remove any contaminated clothing and wash before reuse. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water.

7. HANDLING AND STORAGE INFORMATION

7.1 Work & Hygiene Practices:

Avoid prolonged contact with this material. Avoid breathing the vapors generated by this product. Use in a well ventilated location (e.g., local exhaust ventilation, fans). Wash exposed skin thoroughly with plenty of soap and water after using this product. If necessary, use a moisturizer after washing. Do not eat, drink or smoke while handling this product.

7.2 Storage & Handling:

Use and store in a cool, dry, well ventilated location. Keep away from excessive heat. Keep away from incompatible materials listed in Section 10. Do not store in damaged or unmarked containers or storage devises. Keep containers securely closed when not in use. Open slowly on a level, stable surface. Empty containers may contain residual amounts of this product; therefore, empty containers should be handled with care. As a precaution against exposure to the eyes, nose, throat and face, this product should not be stored higher than waist level. KEEP AWAY FROM CHILDREN AT ALL TIMES!

7.3 Special Precautions:

Do not store where temperatures can exceed 50 °C (122 °F).

	8. E	XPOSURE CONTROLS & PERSONAL PROTECTION	4 of 8
8.1	Ventilation & Engineering Controls:	Use with adequate ventilation (e.g., local exhaust ventilation, fans). Ensure appropriate of equipment is available (e.g., sink, safety shower, eye wash station).	decontaimination
8.2	Respiratory Protection:	No special respiratory protections is required under typical circumstances of use or handling. In instances where vapors or sprays of this product are generated, and respiratory protection is needed, use only protection authorized by 29 CFR § 1910.134, application U.S. State regulations or the Candaian CAS Standard Z94.4-93 and applicable standards of Canadian Provinces, EC Member States or Australia.	
8.3	Eye Protection:	Wear protective eyewear (e.g., safety glasses with side shields) at all times when handling this product. Always use protective eyewear when cleaning spills or leaks. Contact lenses pose a special hazard; soft lenses may absorb and concentrate irritants.	
8.4	Hand Protection:	None required under normal conditions of use. However, may cause skin irritation in some sensitive individuals. When handling large quantities (e.g., >1 gallon [3.785 liters]), wear nitrile or imprevious gloves.	
8.5	Body Protection:	No apron required when handling small quantities. When handling large quantities (e.g., . 1 gallon), eye wash stations and deluge showers should be available. Upon completion of work activities involving large quantities of this product, wash any exposed areas thoroughly with soap and water.	

	9. PHYSICAL & CHEMICAL PROPERTIES		
9.1	Density:	1.1	
9.2	Boiling Point:	NA NA	
9.3	Melting Point:	ND	
9.4	Evaporation Rate:	NA NA	
9.5	Vapor Pressure:	< 1 (air=1)	
9.6	Appearance & Color:	Clear or pigmented liquid	
9.7	Odor Threashold:	NE	
9.8	Solubility:	Not soluble	
9.9	pH:	NA NA	
9.1	Viscosity:	approximately 2,000 cps	
9.11	Flash Point:	43 °C (ASTM D93-15)	
9.12	Other Information:	NA NA	

10. STABILITY & REACTIVITY

10.1 Stability:

Relatively stable under ambient conditions when stored properly.

10.2 Hazardous Decomposition Products:

If exposed to extremely high temperatures, products of thermal decomposition may include irritating vapors and toxic gases (e.g., oxides of carbon and nitrogen).

10.3 Hazardous Polymerization:

Will not occur.

10.4 Conditions to Avoid:

Exposure or contact to extreme temperatures, incompatable chemicals, strong light sources, sparks and flame.

10.5 Incompatable Substances:

Strong oxidizers, peroxides, strong acids or alkalis.

11. TOXICOLOGICAL INFORMATION 5 of 8 11.1 Toxicity Data: This product has NOT been tested on animals to obtain toxicology data. There are toxicology data for the components of the produ t which are found in scientific literature. These data have not been presented in this document. 11.2 Acute Toxicity: See Section 2.5 11.3 Chronic Toxicity: See Section 2.6 11.4 Suspected Carcinogen: The ingredients of this product are not listed as carcinogens by the National Toxicology Program and have not been evaluated by the Internail Agency for Research on Cancer or the American Conference of Government Industrial Hygenists. 11.5 Reproductive Toxicity: This product is not reported to cause reproductive toxicity in humans. Mutagenicity: This product is not reported to produce mutagenic effects in humans. Embryotoxicity: This product is not reported to produce embryotoxic effects in humans. Teratogenicity:

12. ECOLOGICAL INFORMATION

12.1 Environmental Stability:

11.8 Physician Recommendations: Treat syptomatically

11.6 Irritancy of Product:See Section 2.311.7 Biological Exposure Indicies:

This product will slowly volatile from soil. Components of this product will slowly decompose into organic compounds. Butyl Acetate: $K_{OC} = 1.82$. Water Solubility: 120 parts H_2O at 25 °C (77 °F). Bioconcentration Factor = 4-14. Bioconcentration is not anticipated to be significant. This compound can be removed from contaminated environments from volatilization and biodegredation. This compound's half life is 6.1 hours.

12.2 Effects on Plants & Animals:

There is no specific data availble for this product on plant life.

This products is not reported to cause teratogenic effects in humans.

12.3 Effects on Aquatic Life:

There is no specific data availble for this product on aquatic life.

13. DISPOSAL CONSIDERATIONS

13.1 Waste Disposal:

Dispose inaccordance with local, state and Federal waste laws.

13.2 Special Considerations:

This material becomes an inert plastic upon prolonged exposure to sources of UV light and sunlight. Disposal of inert plastics is safer for the environment and is more easily handled for disposal according to local, state and Federal regulations.

	14. TRANSPORTATION INFORMATION	6 of 8
1	asic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transpicional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG, SCT, ADR and the CTDGR.	ortation.
	49 CFR (GRD):	
	Not Regulated	
14.2	IATA (AIR):	
	Not Regulated	
14.3	IMDG (OCN):	
	Not Regulated	
14.4	TDGR (Canadian GND):	
	Not Regulated	
14.5	ADR/RID (EU):	
	Not Regulated	
14.6	MEXICO (SCT):	
	Not Regulated	
14.7	ADGR (AUS):	
	Not Regulated	
	15. REGULATORY INFORMATION	
15.1	SARA Reporting:	
	NA NA	
15.2	SARA Threshold Planning Quantity:	
	NA .	
15.3	TSCA Inventory Status:	
	All components of this product are listed in the TSCA Inventory or are exempt	
15.4	CERCLA Reportable Quantity (RQ):	
	BUTYL ACETATE: 5,0000 lbs (2,270 kg)	
15.5	Other Federal Requirements:	
	This products complies with the appropriate sections of the Food and Drug Administration's 21 CFR subchapter G (Cosmetic	s).
15.6	Other Canadian Regulations:	
	This product has been classified according to the hazard criteria of the CPR and the SDS contains all of the information	(T)
	required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product	•
	are on the Priorities Substances List.	
15.7	State Regulatory Information:	
	Butyl Acetate is listed on the following state criteria list(s): Deleware Air Quality Management List (DE), Massachusetts Haza	
	List (MA), Minnesota Hazardous Substances List (MN), New Jersery Right-to-Know List (NJ), Pennsylvania Right-to-Know List	(PA), and
	Washington Permissible Exposure Limits for Air Contaminants (WA).	
	No other ingredients in this producd, present in a concentration of 1.0% or greater, are listed on any of the following state of	
	California Proposition 65 (CA), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts	
	Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances list, (MN), New Jersey Right-t	
	new Yord Hazardous Substances List (NY), Pennsylvania Right-to-Know list (PA), Washington Permissible Exposures List (WA), Wisconsin
	Hazardous Substances List (WI)	
15.8	67/548/EEC (European Union), Australian NOHSC:2011 (2003), and GHS Requirements:	
	The primary cononents of this product are not listed in Annex 1 of EU Directive 67/548/EEC.	
	Butyl Acetate: Flammable (F). Harmful (Xi).	
	Risk Phrases (R): H226 - Flammable liquid. H315 - Irritating to eyes, skin and respiratory system. H317 - May cuase an	
	allergic skin reaction. Safety Phrases (S): 2-23-29 - Keep out of reach of Children. Do not breath gas, fumes, vapor or spray.	
	Do not empty into drains. Keep away from sources of ignition - No Smoking. Avoid contact with skin and eyes, rinse	
	immediately with plenty of water and seek medical advice.	

16. OTHER INFORMATION

16.1 Other Information:

WARNING! MAY CAUSE AN ALLERGIC SKIN REACTION. CAUSES EYE IRRITATION. Avoid breathing fume, gas, mist, vapors, spray. Wear potective gloves and eye/face protection. IF ON SKIN - Wash with soap and water. IF IN EYES - Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing. If skin irritation or a rash occurs - get medical advice/attention. Do not take internally. Keep away from heat and open flame. KEEP OUT OF THE REACH OF CHILDREN.

16.2 Terms & Definitions:

Please see last page of this SDS.

16.3 Disclaimer:

This Safety Data Sheet (SDS) is offered persuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other governemen regulations must be reviewed for applicability to this product. To the best of Shipmate's and McConnell Labs' knowledge, the information contained herein is reliable and accurate as of the date it was prepared; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to sonsult the latest edition.

16.4 Prepared for:

McConnell Labs, Inc. 406 SW Umatilla Ave Redmond, OR 97756 USA Tel: +1 541 526 1417 Fax: +1 541 526 1418 http://www.lightelegance.com



16.5 Prepared by:

ShipMate, Inc. PO Box 787

Sisters, OR 97759-0787 USA

Tel: +1 541 370 3600 Fax: +1 541 370 5700

email: shipmate@shipmate.com



DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No.	Chemical Abstract Service Number

EXPOSURE LIMITS IN AIR:

ACGIH American Conference on Governmental Industrial Hygienists	
TLV Threshold Limit Value	
OSHA U.S. Occupational Safety and Health Administration	
PEL Permissible Exposure Limit	
IDLH	Immediately Dangerous to Life and Health

FIRST AID MEASURES:

Cardiopulmonary resuscitation - method in which a person whose heart has
stopped receives manual chest compressions and breathing to circulate blood
and provide oxygen to the body.

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS


HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard	
1	Slight Hazard	
2	Moderate Hazard	
3	Severe Hazard	
4	Extreme Hazard	



PERSONAL PROTECTION RATINGS:

Α			
В			
С		盘	
D			
Е			
F			9













Respirator

Face Shield &





Dust & Vapor Half-Mask Respirator

Synthetic Apron Full Face

ग Airline Hood/Mask or SCBA

OTHER STANDARD ABBREVIATIONS:


NA	Not Available
NR	No Results
NE	Not Established
ND	Not Determined
ML	Maximum Limit
SCBA	Self-Contained Breathing Apparatus

NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:							
Autoignition Minimum temperature required to initiate combustion in air with no otl Temperature source of ignition							
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source						
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source						

HAZARD RATINGS:

0	Minimal Hazard		
1	Slight Hazard		
2	Moderate Hazard		
3 Severe Hazard			
4	Extreme Hazard		
ACD	Acidic		
ALK	Alkaline		
COR Corrosive			
W	Use No Water		
OX Oxidizer			
TREFOIL Radioactive			



TOXICOLOGICAL INFORMATION:

LD ₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals s			
LC ₅₀	Lethal concentration (gases) which kills 50% of the exposed animal			
ppm	Concentration expressed in parts of material per million parts			
TD _{lo} Lowest dose to cause a symptom				
TCLo	Lowest concentration to cause a symptom			
TD _{io} , LD _{io} , & LD _o or	Lowest dose (or concentration) to cause lethal or toxic effects			
TC, TCo, LCio, & LCo				
IARC	International Agency for Research on Cancer			
NTP	National Toxicology Program			
RTECS	Registry of Toxic Effects of Chemical Substances			
BCF	Bioconcentration Factor			
TL _m	Median threshold limit			
log Kow or log Koc	Coefficient of Oil/Water Distribution			

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System					
DOT	U.S. Department of Transportation					
TC	Transport Canada					
EPA	U.S. Environmental Protection Agency					
DSL	DSL Canadian Domestic Substance List					
NDSL	Canadian Non-Domestic Substance List					
PSL	Canadian Priority Substances List					
TSCA	U.S. Toxic Substance Control Act					
EU	European Union (European Union Directive 67/548/EEC)					
WGK	Wassergefährdungsklassen (German Water Hazard Class)					

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

0	(4)	(A)	@	((1)		R
Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

EC (67/548/EEC) INFORMATION:

==	1 2 2 4		*		Q	X	×	
С	Е	F	N	0	Т	Xi	Xn	
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful	

CLP/GHS (1272/2008/EC) PICTOGRAMS:

				THE STATE OF THE S		!		
GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment